

Compact C-3-8 Ceiling VAD c/w 91dB sounder, white

Part No. **BF451A/CX/SW**



Overview

Third-party certified to EN54-3 (Sounders), EN54-23 (VADs) and 17 (Isolators) by Intertek.

Provides 'C-3-8' light distribution when ceiling mounted (min 0.4 lux over a 3 x 8m cylindrical area).

Can also provide 'W-3-3.1' light distribution when wall mounted (min. 0.4 lux over a 3 x 3.1m cuboid area).

Impressive 91dB(A) sound output @ 1m.

Onboard short-circuit loop isolator.

550µA quiescent current.

14mA alarm current @24V DC (VAD lit, sounder on max).

Group addressing facility allows multiple devices to be operated simultaneously.

7 selectable volume levels and up to 15 selectable tone pairs.

IP21C rated.

Technical Specifications

Approvals/certifications	Certified to EN54-3, 23 & 17 by Intertek.
Protocol/compatibility	Compatible with C-TEC's XFP/ZFP XP95/Discovery Addressable Fire Panels.
Application/operation	Provides C-3-8 coverage when ceiling mounted. Alternatively can be wall mounted to provide W-3-3.1 coverage.
VAD category & coverage	C-3-8 (151m ³ cylindrical coverage): W-3-3.1 (30m ³ cuboid coverage).
Flash rate & colour	0.5Hz / White.
Supply/operating voltage	17 to 28V DC (Sounder); 21 to 28V DC (Sounder/VAD).
Quiescent current	550µA @ 24 VDC.
Nominal SPL (Sound Pressure Level)	91dB(A) when set to tone 1.
Alarm current	14mA (VAD lit, Sounder on max).



Indicators	Polling (green LED) & Short Circuit Isolator Active (amber LED).
Product dimensions (mm)	102mm diameter x 63mm deep (not including optional XP95/Discovery and base).
IP Rating	IP21C (Type A).
Weight	175g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom